

■ナイロンリベット


(スナップリベット / プッシュリベット)



材質：6ナイロン / UL94V-2


<特徴>

- ・ **抜群の作業性** ハンドワークで使用できます。
- ・ 弾性を生かし、緩み・脱落が発生しにくい。
- ・ 錆びや薬品腐食が発生しません。
- ・ 絶縁体ですので感電が起きません。
- ・ 耐熱仕様もラインナップ。



マイナス

リベット軸径
2.0 / 2.6 / 3.0



プラス

リベット軸径
3.5 / 4.0 / 5.0 / 6.0

品番	色	取付 穴径	取付板厚	D	A	L	d	抜去力	割形状
PN2024	白 / 黒	2.1-2.2	0.6 - 1.2	4.2	1.2	2.4	2.0	3 kg	(-)
PN2032			1.3 - 2.0			3.2			
PN2040			2.1 - 2.8			4.0			
PN2048			2.9 - 3.6			4.8			
PN2056			3.7 - 4.4			5.6			
PN2064			4.4 - 5.2			6.4			
PN2632	白 / 黒	2.7-2.8	1.0 - 2.0	5.0	1.4	3.2	2.6	5 kg	(-)
PN2642			2.0 - 3.0			4.2			
PN2648			2.7 - 3.6			4.8			
PN2655			3.4 - 4.3			5.5			
PN2664			4.3 - 5.2			6.4			
PN2672			5.1 - 6.0			7.2			
PN3035	白 / 黒	3.1-3.2	1.0 - 2.0	6.4	1.6	3.5	3.0	8 kg	(-)
PN3045			2.0 - 3.0			4.5			
PN3050			2.5 - 3.5			5.0			
PN3055			3.0 - 4.0			5.5			
PN3065			4.0 - 5.0			6.5			
PN3075			5.0 - 6.0			7.5			
PN3080			5.5 - 6.5			8.0			
PN3090			6.5 - 7.5			9.0			
PN3100			7.5 - 8.5			10.0			
PN3145			11.5 - 12.5			14.5			
PN3230			20.5 - 21.5			23.0			

品番	色	取付 穴径	取付板厚	D	A	L	d	抜去力	割形状
PN3535	白 / 黒	3.6-3.7	1.2 - 2.1	6.4	1.6	3.5	3.5	12 kg	(+)
PN3545			2.1 - 3.0			4.5			
PN3550			2.7 - 3.6			5.0			
PN3555			3.0 - 4.0			5.5			
PN3560			3.7 - 4.6			6.0			
PN3570			4.5 - 5.5			7.0			
PN3580			5.5 - 6.5			8.0			
PN4040	白 / 黒	4.1-4.2	1.7 - 2.5	8.0	1.8	4.0	4.0	20 kg	(+)
PN4050			2.5 - 3.5			5.0			
PN4055			3.0 - 4.0			5.5			
PN4060			3.5 - 4.5			6.0			
PN4070			4.5 - 5.5			7.0			
PN4080			5.5 - 6.5			8.0			
PN4090			6.5 - 7.5			9.0			
PN4100			7.5 - 8.5			10.0			
PN4120			9.0 - 10.5			12.0			
PN4155			12.5 - 14.0			15.5			
PN5045	白 / 黒	5.1-5.2	1.5 - 2.5	9.0	2.2	4.5	5.0	25 kg	(+)
PN5055			2.5 - 3.5			5.5			
PN5065			3.5 - 4.5			6.5			
PN5075			4.5 - 5.5			7.5			
PN5085			5.5 - 6.5			8.5			
PN5095			6.5 - 7.5			9.5			
PN5105			7.5 - 8.5			10.5			
PN5865	白 / 黒	5.9-6.0	3.0 - 4.5	12.0	2.7	6.5	5.8	25 kg	(+)
PN6060	白 / 黒 / 原色	6.1-6.2	2.5 - 4.0	12.0	3.0	6.0	6.0	30 kg	(+)
PN6080			3.5 - 5.5			8.0			
PN6260	白 / 黒		21.5 - 23.5			26.0			
PN6285			23.5 - 25.5			28.5			



有限会社フジロック



☎ 042-627-9361 / 📠 042-628-0923 / E-mail : mail@fujirokku.jp